

BRP Manufacturing Company

637 North Jackson Street
Lima, Ohio 45801
Phone: 800-858-0482
www.brpmfg.com



Butyl Tape "Rubba Tape" BRP 607

"Rubba Tape" is an extremely tacky self-adhering "uncured" rubber material. This material is used in architectural designs of buildings, vehicles, and water vessels as a watertight seal around windows or doorframes or where metal panels are joined together. It may also be used as an anti-squeak absorption buffer or vibration eliminator in metal-to-metal applications in the building of trucks and buses.

"Rubba Tape" has shown that during accelerated weather testing, no loss of flexibility or resiliency, and no surface cracking after 1300 hours of weathering exposure occurred. It was also able to withstand sub-zero temperatures (-70°F) with no adverse effects.

When ozone tested at 100 pphm for 72 hours at 150°F, **"Rubba Tape"** exhibits no deterioration of material. Therefore, a very long service life under high degrees of ozone concentration is anticipated. **"Rubba Tape"** is available in 1/32" through 1/8" thickness and widths of 1/4" through 36". It can also be custom slit to virtually any required width.

"Rubba Tape" is fabric reinforced to eliminate stretching and prevent creeping or extruding in service.

"Rubba Tape" conforms to FMVSS-302

Testing completed April 2008

|